

**Wyoming Department of Environmental Quality
Water Quality Division
WYPDES Program**

STATEMENT OF BASIS
NEW

APPLICANT NAME: Pinnacle Gas Resources, Inc.

MAILING ADDRESS: 1 East Alger, Suite 206
Sheridan, WY 82801

FACILITY LOCATION: Squaw Creek POD, which is located in the SWSW and the SESE, Section 24, Township 55 North, Range 74 West, and in the SESW, Section 26, the NWNE, Section 27, the SENW and SWSW, Section 28, the NWNW, Section 29, the SENE, Section 32, and the NENE, Section 33, Township 55 North, Range 73 West, Campbell County. The produced water will be discharged into various on-channel reservoirs (3B) located on various unnamed, ephemeral tributaries (3B) of Squaw Creek (3B), and South Squaw Creek (3B). Squaw Creek (3B) is tributary to the Little Powder River (2AB), via Horse Creek (3B). The permit establishes a total maximum daily flow limit of 2.09 MGD, and requires that the produced water being discharged by this facility originate in one or more of the following coal seams: the Pawnee, Cook, Canyon, Wall, and/or Anderson coal seams.

NUMBER: WY0053651

General Facility Description

This facility is a typical coal bed methane production facility in which groundwater is pumped from a coal bearing formation resulting in the release of methane from the coal bed. The permit authorizes the discharge to the surface of groundwater produced in this way provided the effluent quality is in compliance with effluent limits that are established by this permit. In developing effluent limits, all federal and state regulations and standards have been considered and the most stringent requirements incorporated into the permit. The *EPA Effluent Guidelines and Standards for Oil and Gas Extraction Point Source Category (Part 435, Subpart E)* predate the development of coal bed methane extraction technology; however the technology is similar enough to conventional gas extraction that, in the professional judgment of the WDEQ, this effluent limit guideline is appropriately applied to coal bed methane gas production. The guideline limits oil and grease effluent concentrations to less than 35 mg/l and requires that discharges of produced water be used for agricultural production and/or wildlife propagation. This permit does not cover activities associated with discharges of drilling fluids, acids, stimulation waters or other fluids derived from the drilling or completion of the wells.

The permittee has chosen option 2 of the coal bed methane permitting options. Under this permitting option, the produced water is immediately discharged to a class 2 or 3 receiving stream which is eventually tributary to a class 2 perennial water of the state. The permit establishes effluent limits for the end of pipe, which are protective of all the designated uses defined in *Chapter 1 of Wyoming Water Quality Rules and Regulations*. This may include drinking water, game and non-game fish, fish consumption, aquatic life

other than fish, recreation, agriculture, wildlife, industry and scenic value. The permittee has submitted documentation verifying that there is irrigation occurring downstream of this facility on Squaw and Horse Creeks, prior to the closest class 2 water. The permittee has submitted information related to ambient water quality, mixing analyses, and water budgets that demonstrate that the produced water from the different coal seams proposed for development at this facility, when blended, will achieve effluent limits for SAR and specific conductance that have been established in the drainage to protect for agricultural uses. Therefore, the permittee is not required to contain the discharges within the on-channel reservoirs.

Review of the permit application reveals that the outfalls being permitted for discharge is located approximately 36 miles upstream of the Little Powder River - Horse Creek confluence.

Effluent Limits

Permit effluent limits are based on federal and state regulations and are effective as of the date of issuance. The permit requires that the pH must remain within 6.5 and 9.0 standard units. Effluent limits for total dissolved solids (5,000 mg/l), specific conductance (7500 micromhos/cm), and sulfates (3,000 mg/l) are included to protect for stock and wildlife watering. These limits are based upon Wyoming Water Quality Rules and Regulations, Chapter 2 and apply to discharges from all permitted outfalls.

The permit also establishes a dissolved manganese limit of 720 µg/l, and a chlorides limit of 46 mg/l. These limits are based on chronic aquatic life standards for class 2AB waters as established in *the Wyoming Water Quality Rules and Regulations, Chapter 1*. The permit also establishes a total barium limit of 1800 µg/l and a total arsenic limit of 3.6 µg/l, these limits are based on Water Quality Criteria as established in *the Wyoming Water Quality Rules and Regulations, Chapter 1*, for Human Health values. The limits established in this permit for metals and chlorides reflect the application of the antidegradation provisions required under *the Wyoming Water Quality Rules and Regulations, Chapter 1*.

In addition, the permit establishes a dissolved iron limit of 1000 µg/l, which is based upon chronic aquatic life standards for class 3B waters greater than one mile from the confluence of a class 2 water, and reflects the application of standards required under *Chapter 1 of the Wyoming Water Quality Rules and Regulations*. All limits described in this section are intended to protect for the above listed designated uses, on both the immediate receiving water and the perennial mainstem, and apply at the end of pipe

A limit for total recoverable aluminum – 750 µg/l – is also being established in this permit. This limit is based upon the acute aquatic life standard established in *Chapter 1 of the Wyoming Water Quality Rules and Regulations*. In the case of total recoverable aluminum, the chronic aquatic life value does not apply, based upon the hardness and pH of the receiving stream. This limit applies at the end of pipe.

The water balances and mixing calculations submitted in support of the permit application were based on a maximum effluent flow of 2.09 MGD, and water quality representative of the Pawnee, Cook, Canyon, Anderson, and/or Wall coal seams. Therefore, the permit establishes a total maximum daily flow limit of 2.09 million gallons per day (MGD), to be calculated as the sum of all discharge from all permitted outfalls, and requires that the produced water being discharged by this facility originate in one or more of the following coal seams: the Pawnee, Cook, Canyon, Anderson, and/or Wall coal seams.

Irrigation Protection

In order to monitor and regulate coal bed methane discharge for compliance with Chapter 1, Section 20 (protection of agricultural water supply), effluent limits for sodium adsorption ratio (SAR) and specific

conductance (EC) are included in this permit. The Wyoming DEQ has determined that an SAR of 11 and specific conductance of 2,000 micromhos/cm is intended to be protective of agriculture use in the Squaw and Horse Creek drainages. The specific conductance limit of 2,000 micromhos/cm is based on the threshold value for alfalfa, which is considered to be the most salt sensitive plant irrigated in the Squaw and Horse Creek drainages downstream from this facility. (*USDA George E. Brown Jr. Salinity Laboratory, Salt Tolerance Database, Grasses and Forage Crops*). Data to characterize the salt tolerance of alfalfa specific to the Squaw and Horse Creek drainages is currently unavailable. The SAR limit of 11 was determined to not reduce the rate of infiltration of irrigated soils in the Squaw and Horse Creek drainages, given the specific conductance threshold referenced above as ascertained from *Figure 3 (page 44) of Agricultural Salinity and Drainage, Hanson et al., 1999 revision*.

The application for WYPDES permit WY0046213, which was utilized by the WDEQ in establishing effluent limits protective of irrigation on Wild Horse Creek, describes the downstream irrigation use on Squaw and Horse Creek as passive systems which automatically divert water from Squaw and Horse Creeks on to the irrigated fields whenever there is flow in either Squaw or Horse Creeks. As the permittee has demonstrated that the blended effluent will be able to achieve effluent limits for SAR and EC that are protective of irrigation uses within Squaw and Horse Creek, the permit establishes end-of-pipe effluent limits for SAR = 11, and EC = 2000 micromohs/cm.

Monitoring and Reporting

The permit requires sampling at a designated tributary water quality monitoring station located on the receiving stream – Horse Creek, and at mainstem water quality monitoring station locations on the Little Powder River upstream and downstream of the Horse Creek - Little Powder River confluence, located as described in Table 1, Part I.B.12 of the following permit. Water quality monitoring stations on the Little Powder River will be located in the main channel of the Little Powder River outside of the mixing zone of Horse Creek and the Little Powder River. Effluent samples at the designated water quality monitoring stations must be collected on a monthly basis and are to be reported semiannually. Samples taken in compliance with the monitoring requirements specified above shall be taken at the following locations: designated water quality monitoring stations identified as TRIB1, ULPR, and DLPR in Table 1, Part I.B.12 of the permit below. Established water quality monitoring stations on the mainstem are to be located outside the mixing zone with the tributary and the mainstem. Monthly water quality samples are to be collected at all three water quality monitoring stations when effluent from this CBM facility reaches the TRIB1 station on Horse Creek. If flow occurs at the TRIB1 station during a given monthly monitoring period, but this CBM facility did not contribute to that flow, the permittee will report “did not contribute” in the discharge monitoring reports for that monthly monitoring period. Under such circumstances, sampling is not required at the three water quality monitoring stations, and it will be the responsibility of the permittee to demonstrate that the effluent from this facility did not contribute to the flow occurring at the TRIB1 station. If no flow occurs at the TRIB1 station for an entire monthly monitoring period, then “no flow” is to be reported and samples need not be collected at the three water quality monitoring stations for that monthly monitoring period.

At the designated water quality monitoring stations, monitoring will be required for calcium, magnesium, sodium, sodium adsorption ratio and specific conductance. Information gathered from the water quality monitoring stations may result in modification of the permit to protect existing uses on the tributary and mainstem. Established water quality monitoring stations on the mainstem are to be located outside the mixing zone of the tributary with the mainstem

Results are to be reported twice-yearly and if no discharge occurs at the outfall then "no discharge" is to be reported. The permit also requires that an initial monitoring of the effluent be conducted within the first 60 days of discharge and the results submitted to WDEQ and the U.S. Environmental Protection Agency within 120 days of the commencement of discharge.

General Requirements

Reservoir and/or discharge water is to be released at a rate which does not cause significant erosion to the channel or receiving lands.

There shall be no discharge of floating solids or visible foam in other than trace amounts, nor shall the discharge cause formation of visible deposits of iron, hydrocarbons or any other constituent on the bottom or shoreline of the receiving water. In addition, erosion control measures will be implemented to prevent significant damage to or erosion of the receiving water channel at the point of discharge.

The discharge of wastewater and the effluent limits that are established in this permit have been reviewed to ensure that the levels of water quality necessary to protect the designated uses of the receiving waters are maintained and protected. An antidegradation review has been conducted and verifies that the permit conditions, including the effluent limitations established, provide a level of protection to the receiving water consistent with the antidegradation provisions of Wyoming surface water quality standards.

Self monitoring of effluent quality and quantity is required on a regular basis with reporting of results semiannually. The permit is scheduled to expire on December 31, 2007, which is reflective of the WDEQ's efforts towards watershed permitting and similar expiration dates for all permits within a specific drainage, which will allow for basin-wide analysis upon renewal of the permits in the drainage.

Kathy Shreve
Water Quality Division
Department of Environmental Quality
Drafted: September 23, 2005

AUTHORIZATION TO DISCHARGE UNDER THE
WYOMING POLLUTANT DISCHARGE ELIMINATION SYSTEM

In compliance with the provisions of the Federal Water Pollution Control Act, (hereinafter referred to as "the Act"), and the Wyoming Environmental Quality Act,

Pinnacle Gas Resources, Inc.

is authorized to discharge from the wastewater treatment facilities serving the

Squaw Creek POD,

which is located in the

SWSW and the SESE, Section 24, Township 55 North, Range 74 West, and in the SESW, Section 26, the NWNE, Section 27, the SENW and SWSW, Section 28, the NWNW, Section 29, the SENE, Section 32, and the NENE, Section 33, Township 55 North, Range 73 West, Campbell County,


to receiving waters named

various on-channel reservoirs (3B) located on various unnamed, ephemeral tributaries (3B) of Squaw Creek (3B), and South Squaw Creek (3B). Squaw Creek (3B) is tributary to the Little Powder River (2AB), via Horse Creek (3B),


in accordance with effluent limitations, monitoring requirements and other conditions set forth in Parts I, II and III hereof.

This permit shall become effective on the date of signature by the Director of the Department of Environmental Quality.

This permit and the authorization to discharge shall expire December 31, 2007, at midnight.


John F. Wagner
Administrator - Water Quality

11/24/06
Date


John V. Corra
Director - Department of Environmental Quality

1/24/06
Date

PART I

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

Effective immediately and lasting through December 31, 2007, the quality of effluent discharged by the permittee shall, at a minimum, meet the limitations set forth below. The permittee is authorized to discharge from outfall(s) serial numbers 001-010.

1.a. Discharges from all outfalls are limited as specified below:

Effluent Limits

<u>Effluent Characteristic</u>	<u>Daily Maximum Outfall</u>
Chlorides, mg/l	46
Dissolved Iron, µg/l	1000
Dissolved Manganese, µg/l	720
pH, standard units	6.5 – 9.0
Specific Conductance, micromhos/cm	2000
Sulfates, mg/l	3000
Sodium Adsorption Ratio, calculated as an unadjusted for bicarbonate ratio	11
Total Recoverable Aluminum, µg/l	750
Total Arsenic, µg/l	3.6
Total Barium, µg/l	1800
Total Dissolved Solids, mg/l	5000
Total Flow, MGD*	2.09

*Total flow is to be calculated as the sum of all discharge from all permitted outfalls. The permit requires that the produced water being discharged by this facility originate in one or more of the following coal seams: the Pawnee, Cook, Canyon, Anderson, and/or Wall coal seams.

The pH shall not be less than 6.5 standard units nor greater than 9.0 standard units in any single grab sample.

The permittee may, if so desired, discharge effluent from any authorized well to any permitted outfall, as long as all permit limits and requirements can be met. This facility, as originally permitted, consisted of 10 outfalls and 122 wells.

Information gathered from the water quality monitoring stations may result in modification of the permit to protect existing uses on the tributary and the mainstem.

There shall be no discharge of floating solids or visible foam in other than trace amounts, nor shall the discharge cause formation of a visible sheen or visible hydrocarbon deposits on the bottom or shoreline of the receiving water.

All waters shall be discharged in a manner to prevent erosion, scouring, or damage to stream banks, stream beds, ditches, or other waters of the state at the point of discharge. In addition, there shall be no deposition of substances in quantities which could result in significant aesthetic degradation, or degradation of habitat for aquatic life, plant life or wildlife; or which could adversely affect public water supplies or those intended for agricultural or industrial use.

Reservoir and/or discharge water is to be released at a rate which does not cause significant erosion to the channel or receiving lands.

2. a. Monitoring of the initial discharge

Within 60 days of commencement of discharge, a sample shall be collected from each outfall and analyzed for all of the constituents specified below, at the required detection limits. Within 120 days of commencement of discharge, a summary report on the produced water must be submitted to the Wyoming Department of Environmental Quality and the U.S. EPA Region 8 at the addresses listed below. This summary report must include the results and detection limits for each of the constituents listed below. In addition, the report must include written notification of the established location of the discharge point (refer to Part I.B.11). This notification must include a confirmation that the location of the established discharge point(s) is within 1,510 feet of the location of the identified discharge point(s), is within the same drainage, and discharges to the same landowner's property as identified on the original application form. The legal description and location in decimal degrees of the established discharge point(s) must also be provided. After receiving the monitoring results for the initial discharge, the effluent limits and monitoring requirements established in this permit may be modified.

<u>Parameter*</u> (See notes following the table on chemical states)	<u>Required Detection Limits and Required Units</u>
Alkalinity, Total	1 mg/l as CaCO ₃
Aluminum, Total Recoverable	50 µg/l
Arsenic, Total	1 µg/l
Barium, Total	100 µg/l
Bicarbonate	10 mg/l
Cadmium, Dissolved	5 µg/l
Calcium, Dissolved	50 µg/l, report as me/l
Calcium, Dissolved	50 µg/l, report as mg/l
Chlorides	5 mg/l
Copper, Dissolved	10 µg/l
Dissolved Solids, Total	5 mg/l
Hardness, Total	10 mg/l as CaCO ₃

Parameter* (See notes following the table on chemical states)	Required Detection Limits and Required Units
Iron, Dissolved	50 µg/l
Lead, Dissolved	2 µg/l
Magnesium, Dissolved	100 µg/l, report as me/l
Magnesium, Dissolved	100 µg/l, report as mg/l
Manganese, Dissolved	50 µg/l
Mercury, Dissolved	1 µg/l
pH	to 0.1 pH unit
Radium 226, Total	0.2 pCi/l
Selenium, Total Recoverable	5 µg/l
Sodium Adsorption Ratio	Calculated as unadjusted ratio
Sodium, Dissolved	100 µg/l, report as me/l
Sodium, Dissolved	100 µg/l, report as mg/l
Specific Conductance	5 micromhos/cm
Sulfates	10 mg/l
Zinc, Dissolved	50 µg/l

TOTAL: Value is expressed in terms of total recoverable metal in the water column.

NOTE: Except for aquatic life values for metals and where otherwise indicated, the values given refer to the total recoverable (dissolved plus suspended) amount for each substance. For the aquatic life values for metals, the values refer to the dissolved amount.

DISSOLVED: Value is based on the dissolved amount which is the amount that will pass through a 0.45 µm membrane filter prior to acidification to pH 1.5 - 2.0 with nitric acid.

Initial monitoring reports are to be sent to the following addresses:

Planning and Targeting Program, 8ENF-PT
Office of Enforcement, Compliance, and Environmental Justice
U.S. EPA Region 8
999 18th St., Suite 300
Denver, CO 80202-2466

and

Wyoming Department of Environmental Quality
Water Quality Division
Herschler Building, 4 West
122 West 25th Street
Cheyenne, WY 82002

b. Routine monitoring End of Pipe – 001-010

For the duration of the permit, at a minimum, samples for the constituents described below shall be collected at the indicated frequencies. The first routine monitoring for the time frame during which the monitoring of initial discharge occurs will, at a minimum, consist of flow measurements for the duration of the six-month monitoring

time frame. Monitoring will be based on semi-annual time frames, from January through June, and from July through December.

<u>Parameter</u>	<u>Measurement Frequency</u>	<u>Sample Type</u>
Bicarbonate (mg/l)	Once Every Three Months	Grab
Dissolved calcium (mg/l)	Once Every Three Months	Grab
Dissolved calcium (me/l)	Once Every Three Months	Grab
Chloride (mg/l)	Annually	Grab
Dissolved Iron (µg/l)	Annually	Grab
Dissolved Manganese (µg/l)	Annually	Grab
Dissolved Magnesium (mg/l)	Once Every Three Months	Grab
Dissolved Magnesium (me/l)	Once Every Three Months	Grab
pH (standard units)	Once Every Three Months	Grab
Dissolved Sodium (mg/l)	Once Every Three Months	Grab
Dissolved Sodium (me/l)	Once Every Three Months	Grab
Sodium Adsorption Ratio (unadjusted)	Once Every Three Months	Calculated
Specific Conductance (micromohs/cm)	Once Every Three Months	Grab
Sulfate (mg/l)	Annually	Grab
Total Alkalinity (mg/l)	Once Every Three Months	Grab
Total Arsenic (µg/l)	Annually	Grab
Total Barium (µg/l)	Annually	Grab
Total Flow - (MGD)	Monthly	Continuous
Total Recoverable Aluminum (µg/l)	Annually	Grab

Samples taken in compliance with the monitoring requirements specified above shall be taken at the following location(s): At the outfall of the final treatment unit which is located out of the natural drainage and prior to admixture with diluent waters.

c. Water Quality Monitoring Stations TRIB1, ULPR, DLPR

For the duration of the permit, at a minimum, samples for the constituents described below shall be collected at the indicated frequencies. Monitoring will be based on monthly time frames, and reported semiannually.

<u>Parameter</u>	<u>Measurement Frequency</u>	<u>Sample Type</u>
Dissolved Calcium (mg/l)	Monthly	Grab
Dissolved Calcium (me/l)	Monthly	Grab
Dissolved Magnesium (mg/l)	Monthly	Grab
Dissolved Magnesium (me/l)	Monthly	Grab
Dissolved Sodium (mg/l)	Monthly	Grab
Dissolved Sodium (me/l)	Monthly	Grab
Sodium Adsorption Ratio (calculated as unadjusted ratio)	Monthly	Calculated
Specific Conductance (micromohs/cm)	Monthly	Grab
Flow* (MGD)	Monthly	Instantaneous
Temperature, degrees Celsius	Monthly	Grab

*The permittee is only required to monitor and report flow at the tributary monitoring station on Horse Creek (TRIB1). The permittee is not required to monitor or report flow data at the mainstem water quality monitoring stations (ULPR and DLPR), see Table 1, Part I.B.12 for location descriptions.

Samples taken in compliance with the monitoring requirements specified above shall be taken at the following locations: designated water quality monitoring stations identified as TRIB1, ULPR, and DLPR in Table 1 (located at the end of Part I) of the permit below. Established water quality monitoring stations on the mainstem are to be located outside the mixing zone with the tributary and the mainstem. Monthly water quality samples are to be collected at all three water quality monitoring stations when effluent from this CBM facility reaches the TRIB1 station on Horse Creek. If flow occurs at the TRIB1 station during a given monthly monitoring period, but this CBM facility did not contribute to that flow, the permittee will report "did not contribute" in the discharge monitoring reports for that monthly monitoring period. Under such circumstances, sampling is not required at the three water quality monitoring stations, and it will be the responsibility of the permittee to demonstrate that the effluent from this facility did not contribute to the flow occurring at the TRIB1 station. If no flow at all occurs at the TRIB1 station for an entire monthly monitoring period, then "no flow" is to be reported and samples need not be collected at the three water quality monitoring stations for that monthly monitoring period.

B. MONITORING AND REPORTING

1. Representative Sampling

Samples and measurements taken as required herein shall be representative of the volume and nature of the monitored discharge. All samples shall be taken at the monitoring points specified in this permit and, unless otherwise specified, before the effluent joins or is diluted by any other waste stream, body of water, or substance. Monitoring points shall not be changed without notification to and approval by the permit issuing authority.

2. **Reporting**

Results of initial monitoring, including the date the discharge began, shall be summarized on a Monitoring Report Form for Monitoring of Initial Discharge and submitted to the state water pollution control agency at the address below postmarked no later than 120 days after the commencement of discharge.

Results of routine end of pipe, irrigation compliance point, and water quality station monitoring during the previous six (6) months shall be summarized and reported semiannually on a Discharge Monitoring Report Form (DMR). If the discharge is intermittent, the date the discharge began and ended must be included. The information submitted on the first semiannual DMR shall contain a summary of flow measurements and any additional monitoring conducted subsequent to the submittal of the initial monitoring report. When required, whole effluent toxicity (biomonitoring) results must be reported on the most recent version of *EPA Region VIII's Guidance for Whole Effluent Reporting*. Monitoring reports must be submitted to the state water pollution control agency at the following address postmarked no later than the 15th day of the second month following the completed reporting period. The first report due following the issuance of this permit is due on August 15, 2006.

Legible copies of these, and all other reports required herein, shall be signed and certified in accordance with the Signatory Requirements contained in Part II.A.11.

Wyoming Department of Environmental Quality
Water Quality Division
Herschler Building, 4 West
122 West 25th Street
Cheyenne, WY 82002
Telephone: (307) 777-7781

If no discharge occurs during the reporting period, "no discharge" shall be reported. If discharge is intermittent during the reporting period, sampling shall be done while the facility is discharging.

3. **Definitions**

- a. The "monthly average" shall be determined by calculating the arithmetic mean (geometric mean in the case of fecal coliform) of all composite and/or grab samples collected during a calendar month.
- b. The "weekly average" shall be determined by calculating the arithmetic mean (geometric mean in the case of fecal coliform) of all composite and/or grab samples collected during any week.
- c. The "daily maximum" shall be determined by the analysis of a single grab or composite sample.
- d. "MGD", for monitoring requirements, is defined as million gallons per day.
- e. "Net" value, if noted under Effluent Characteristics, is calculated on the basis of the net increase of the individual parameter over the quantity of that same parameter present in

the intake water measured prior to any contamination or use in the process of this facility. Any contaminants contained in any intake water obtained from underground wells shall not be adjusted for as described above and, therefore, shall be considered as process input to the final effluent. Limitations in which "net" is not noted are calculated on the basis of gross measurements of each parameter in the discharge, irrespective of the quantity of those parameters in the intake waters.

- f. A "composite" sample, for monitoring requirements, is defined as a minimum of four grab samples collected at equally spaced two hour intervals and proportioned according to flow.
- g. An "instantaneous" measurement for monitoring requirements is defined as a single reading, measurement, or observation.
- h. A "pollutant" is any substance or substances which, if allowed to enter surface waters of the state, causes or threatens to cause pollution as defined in the Wyoming Environmental Quality Act, Section 35-11-103.
- i. "Total Flow" is the total volume of water discharged, measured on a continuous basis and reported as a total volume for each month during a reporting period. The accuracy of flow measurement must comply with Part III.A.1.

4. Test Procedures

Test procedures for the analysis of pollutants, collection of samples, sample containers, sample preservation, and holding times, shall conform to regulations published pursuant to 40 CFR, Part 136, unless other test procedures have been specified in this permit.

5. Recording of Results

For each measurement or sample taken pursuant to the requirements of this permit, the permittee shall record the following information:

- a. The exact place, date and time of sampling;
- b. The dates and times the analyses were performed;
- c. The person(s) who performed the analyses and collected the samples;
- d. The analytical techniques or methods used; and
- e. The results of all required analyses including the bench sheets, instrument readouts, computer disks or tapes, etc., used to determine the results.

6. Additional Monitoring by Permittee

If the permittee monitors any pollutant at the location(s) designated herein more frequently than required by this permit, using approved analytical methods as specified above, the results of such monitoring shall be included in the calculation and reporting of the values required in the Discharge Monitoring Report Form. Such increased frequency shall also be indicated.

7. **Records Retention**

The permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least three years from the date of the sample, measurement, report or application. This period may be extended by request of the administrator at any time. Data collected on site, copies of Discharge Monitoring Reports and a copy of this NPDES permit must be maintained on site during the duration of activity at the permitted location.

8. **Penalties for Tampering**

The Act provides that any person who falsifies, tampers with or knowingly renders inaccurate, any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than two years per violation, or both.

9. **Compliance Schedules**

Reports of compliance or noncompliance with, or any progress reports on interim and final requirements contained in any Compliance Schedule of this permit shall be submitted no later than 14 days following each schedule date.

10. **Facility Identification**

All facilities discharging produced water shall be clearly identified with an all-weather sign posted at each outfall and flow monitoring locations (points of compliance). This sign shall, as a minimum, convey the following information:

- a. The name of the company, corporation, and person who holds the discharge permit, and the NPDES permit number;
- b. The contact name and phone number of the person responsible for the records associated with the permit;
- c. The name of the facility (lease, well number, etc.) and the outfall number as identified by the discharge permit.

11. **Identification and Establishment of Discharge Points**

According to 40 CFR 122.21(k)(1), the permittee shall identify the expected location of each discharge point on the appropriate NPDES permit application form. The location of the discharge point must be identified to within an accuracy of 15 seconds. This equates to a distance of 1,510 feet.

Public notice is not required if the location of the established discharge point is within 1,510 feet of the location of the discharge point originally identified on the permit application. In addition, the discharge must be within the same drainage and must discharge to the same landowner's

property as identified on the original application form. If the three previously stated requirements are not satisfied, modification of the discharge point location(s) constitutes a major modification of the permit as defined in Part I.B.12. The permittee shall provide written notification of the establishment of each discharge point in accordance with Part I.A.2.a above.

12. Location of Outfalls, Irrigation compliance Points, and Water Quality Monitoring Stations

As of the date of permit issuance, authorized points of discharge were as follows:

SEE TABLE 1 FOR A LIST OF OUTFALL, IRRIGATION COMPLIANCE POINTS, AND WATER QUALITY MONITORING STATION LOCATIONS

Requests for modification of the above list will be processed as follows. If the requested modification satisfies the definition of a minor permit modification as defined in 40 CFR 122.63 modifications will not be required to be advertised in a public notice. A minor modification constitutes a correction of a typographical error, increase in monitoring and/or reporting, revision to an interim compliance schedule date, change in ownership, revision of a construction schedule for a new source discharger, deletion of permitted outfalls, and/or the incorporation of an approved local pretreatment program.

A request for a minor modification must be initiated by the permittee by completing the form titled Wyoming Pollutant Discharge Elimination System Permit Modification Application For Coal Bed Methane. Incomplete application forms will be returned to the applicant.

The outfalls listed in Table 1 (located at the end of Part I) may be moved from the established location without submittal of a permit modification application provided all of the following conditions are satisfied:

1. The new outfall location is within 2640 feet of the established outfall location.
2. The new outfall location is within the same drainage or immediate permitted receiving waterbody.
3. There is no change in the affected landowners.
4. Notification of the change in outfall location must be provided to the NPDES Permits Section on a form provided by the WQD Administrator within 10 days of the outfall location change. The form must be provided in duplicate and legible maps showing the previous and new outfall location must be attached to the form.

Moving an outfall location without satisfying the four above listed conditions will be considered a violation of this permit and subject to full enforcement authority of the WQD.

An outfall relocation as described above will not be allowed if the new outfall location is less than one mile from the confluence of a Class 2 waterbody and the dissolved iron limits established in the permit for the outfall are based upon Class 3 standards.

Discharge Point # (Outfall)	Immediate Receiving Stream	Distance from outfall to mainstem (stream miles)	Quarter/Quarter	Section	Township	Range	Latitude	Longitude	Reservoir Name	Groundwater approval required before discharge?
001	Unnamed, ephemeral tributary to Squaw Creek	38.95	NWNW	29	55	73	44.721,751N	105.669,444 W	Prairie Dog	YES
002	Squaw Creek	36.47	SENW	28	55	73	44.716,893 N	105.647,868 W	Pink Pig	YES
003	Unnamed, ephemeral tributary to South. Squaw Creek	36.68	SWSW	28	55	73	44.712,472N	105.651,712 W	Mangy Coyote	YES
004	Unnamed, ephemeral tributary to South. Squaw Creek	36.68	SWSW	28	55	73	44.711,503 N	105.650,402 W	Mangy Coyote	YES
005	Unnamed, ephemeral tributary to South. Squaw Creek	38.11	SENE	32	55	73	44.703,138 N	105.657,810 W	Yellow Dog	YES
006	Unnamed, ephemeral tributary to Squaw Creek	35.96	NENE	33	55	73	44.704,180 N	105.638,143 W	Brown Cow	YES
007	Unnamed, ephemeral tributary to Squaw Creek	37.85	NWNE	27	55	73	44.720,839 N	105.626,052 W	Bay Horse	YES
008	Unnamed, ephemeral tributary to Squaw Creek	31.96	SESW	26	55	73	44.711,156 N	105.608,920 W	Shaggy Sheep	YES
009	Unnamed, ephemeral tributary to Squaw Creek	43.15	SWSW	24	55	74	44.72415N	105.71929 W	Leon #1	YES
010	Unnamed, ephemeral tributary to Squaw Creek	41.20	SESE	24	55	74	44.72375 N	105.70276 W	Leon #3	YES
TRIB1	Horse Creek	0.3	SWSE	22	55	71	44.730,217° N	105.377,901° W	N/A	N/A
ULPR	Little Powder River	0	SWSW	23	55	71	44.726,847° N	105.369,292° W	N/A	N/A

C. RESERVOIR / IMPOUNDMENT REQUIREMENTS

1. Groundwater Monitoring Beneath Impoundments

Table 1 of the permit above identifies which outfalls (if any) are designed to discharge into impoundments that are subject to groundwater monitoring requirements established in the latest version of the Water Quality Division guideline *"Compliance Monitoring for Groundwater Protection Beneath Unlined Coalbed Methane Produced Water Impoundments."* These specified outfalls are not authorized to discharge until a written groundwater compliance approval has been granted by the Groundwater Pollution Control Program of the Water Quality Division. A groundwater compliance approval will consist of either a final approved groundwater compliance monitoring plan, or written authorization for an exemption thereof. Once an impoundment has been granted a written groundwater compliance approval, the contributing outfall(s) to that reservoir may commence discharge.

Any discharge into an Impoundment which has not been granted the required groundwater compliance approval will constitute a violation of this permit, and may result in enforcement action from the Water Quality Division to include a notice of violation, revocation of the discharge permit, or other appropriate enforcement action.

