

Cites Changes

Chapter 3

8(c) Monitoring wells shall be designed and constructed to protect groundwater resources according to Chapter ~~4~~ 26 of these regulations.

8(d) Monitoring wells shall be plugged and abandoned in accordance with Chapter ~~4~~ 26 of these regulations.

8(e) The administrator may request information from the owner of a facility permitted by rule to determine whether that facility may be causing a violation of groundwater use standards in Chapter 8 of these regulations, the construction standards found in this chapter and in Chapter 11 and Chapter 25 of these regulations

Chapter 11

Table of Contents – Part D is now Chapter 25, Part G is now Chapter 26.

Part C, Section 27 Domestic Wastes from Commercial/Industrial Facilities Commercial/industrial facilities which generate waste that is entirely domestic waste shall be designed in compliance with Chapter 25 or Part B ~~or Part D~~ of Chapter XI.

Chapter 12

(IX) Well abandonment. Test wells and groundwater sources which are not in use shall be sealed in accordance with requirements of ~~Part G of Chapter 11~~ Chapter 26, Water Quality Rules and Regulations.

Chapter 16

Section 7(v) A requirement that the operator submit the disposal capacity of the facility in gallons per day as calculated using Table 1, ~~Chapter 11, Section 34~~ Chapter 25.

Section 10(a) All Class V facilities must meet or exceed the design standards of these regulations including Part B ~~and G~~ of Chapter 11 and Chapter 26, Water Quality Rules and Regulations.

Section 10 (f)(ii) Conform to applicable construction standards found in ~~Chapter 11, Part D,~~ Chapter 25, Wyoming Water Quality Rules and Regulations; and

Section 10(i)(iv) The subsurface fluid distribution system shall be designed in accordance with general design requirements found in Chapter 25 ~~Chapter 11, Part D~~ .

Section 10(j)(i) Conforms to applicable construction standards found in ~~Chapter 11, Part D,~~ Chapter 25, Wyoming Water Quality Rules and Regulations;

Section 10(j) (iii) Be designed for the maximum daily peak flow determined from Table 1 of ~~Section 34, Chapter 11~~ Chapter 25, Water Quality Rules and Regulations. In addition, whenever multiple points of discharge under one owner within any five (5) acres of land have a design capacity under

~~Chapter 11, Section 34~~ **Chapter 25** to inject more than a total of 2,000 gallons per day of domestic sewage, they shall be permitted under this chapter in the same manner that they would be permitted if all the waste were delivered to a single point of discharge.

Section 10(o) Class 5C6 and 5E5 facilities shall meet the construction standards and separation distances appropriate for the design flow as shown in ~~Chapter 11, Part D,~~ **Chapter 25**.

Chapter 20

Section 32 **Domestic Wastes at Confined Swine Feeding Operations.** No human or domestic waste shall be allowed to mix with animal waste collection, storage, treatment, and disposal operations at a confined swine feeding operation. Separate domestic waste collection and treatment facilities shall be permitted under Chapter 3 and designed according to ~~Chapter 11~~ **Chapter 25** of the Wyoming Water Quality Division Rules and Regulations or by the appropriate local agency delegated permitting authority for small wastewater systems.

Chapter 21

Section 2(b) These regulations are not applicable if the primary intent is to provide treatment and/or disposal of a wastewater. Treatment and disposal are regulated under appropriate sections of Chapter 11 **and Chapter 25**, Wyoming Water Quality Rules and Regulations.

Chapter 23

Section 7(d)(i) Separation of the drainfield relative to groundwater and impervious soils will meet or exceed the minimum standards established in ~~Chapter 11, Part D, Section 36 (e)~~ **Chapter 25** of Wyoming Water Quality Rules and Regulations.

Section 7(d)(ii) Soil percolation rates will meet or exceed the minimum standard established in ~~Chapter 11, Part D, Section 36 (d) and 38 (b)~~ **Chapter 25** of Wyoming Water Quality Rules and Regulations.

Section 7(d)(ii)(A) Percolation tests must be performed according to the procedure described in ~~Chapter 11, Part D,~~ **Chapter 25** Appendix A of Wyoming Water Quality Rules and Regulations or other procedures approved by the department.

Section 7(d)(iii) Topographic slope, or grade, for sufficient area within each lot within the proposed subdivision will meet or exceed the applicable minimum standards established in ~~Chapter 11, Part D~~ **Chapter 25** of

Section 7(d)(viii)(A) Except as provided for in sub-part (B) of this part, where unconfined groundwater is Class I as defined in Chapter 9 of Wyoming Water Quality Rules and Regulations, small wastewater systems designed in accordance with ~~Chapter 11, Part D,~~ **Chapter 25** requirements and these regulations may be used provided that:

Section 7(d)(viii)(B)(I) Small Wastewater systems overlying unconfined Class I groundwater as defined in Chapter 8 of Wyoming Water Quality Rules and Regulations and designed in accordance with ~~Chapter 11, Part D~~ **Chapter 25**, Wyoming Water Quality Rules and Regulations fail to comply with one or more of the standards established in Section 7 (viii) (A) (i) through (III) of this section;.....

Section 7(d)(viii)(D) Where an enhanced treatment system is used it must be constructed and operated in conjunction with a subsurface disposal system that meets or exceeds the requirements of ~~Chapter 11,~~ ~~Part D~~ **Chapter 25**, Wyoming Water Quality Rules and Regulations.